



Pipe PVC-U transparent SDR51/Series S25

Model:

- Material: PVC-U
- Dimension: acc. to DIN 8062
- Colour: transparent - Transparency depends on outer diameter and wall thickness! Chemical and thermal stress can cause discolouration
- Pipe length: 5000mm, with plain ends
- **Note 1:** Dimensional variations of wall thickness not acc. to DIN 8062
- Approval: food grade, with declaration of conformity acc. EU 10/2011 and EU 1953/2004, Approval on request
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.
- * pcs in foil

	Note	d	SDR	Code	Weight	e	di
		(mm)			(kg/m)	(mm)	(mm)
* 5	SDR 34,4	63	34.4	192 017 036	0.571	1.9	59.4
* 3	SDR 41	75	41	192 017 037	0.683	1.9	71.4
* 2		90	51	192 017 038	0.785	1.8	86.4
* 1	1	110	51	192 017 039	1.180	2.2	105.6
* 1		125	51	192 017 040	1.500	2.5	120.0
* 1		140	51	192 017 041	1.860	2.8	134.4
* 1		160	51	192 017 042	2.440	3.2	153.6
* 1		200	51	192 017 044	3.670	3.9	192.0
* 1	1	225	51	192 017 045	4.670	4.4	216.0
* 1		250	51	192 017 046	5.730	4.9	240.2
* 1	1	280	51	192 017 047	7.210	5.5	269.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>