

# Pressure Reducing Valve Type 582



## Product description

A pressure reducing valve reduces the outlet pressure to a specified value.

### Function

Downstream pressure (at the outlet) works against the spring resistance and raises the diaphragm until equilibrium of forces is reached. The desired outlet pressure is regulated by means of the spring pre-tensioning. The inlet pressure is not directly related to the outlet pressure. The pressure at the outlet thus remains constant, despite fluctuations at the inlet.

The diaphragm is not influenced by pressure peaks, meaning sensitive measuring devices can be protected downstream.

The set pressure can be increased by turning the spindle at the top of the valve in a clockwise direction. Turning it counterclockwise reduces the set pressure. Inward-pointing arrows, which visualize the direction of flow and the pressure setting, handling easier. Pressure reducing valves are often used to protect downstream devices against overpressure.

### Applications

- Water treatment
- Chemical process industry
- Semiconductor industry
- Solar industry

### Benefits/features

#### Easy assembly

- Compact design allows installation even when space is limited
- Radially dismountable
- Integrated assembling aid enables direct assembly of the valve
- Significantly shorter installation length thanks to union connections

#### Easy operation

- No re-torquing required thanks to central housing nut
- Easily adjustable set pressure
- Constant and stable control behavior
- Leak-resistant in the event of temperature fluctuations
- Low maintenance
- Pressure setting possible even during operation


**Flexible**

- Manometer available as an option for neutral and aggressive media
- Various connection options available thanks to the spigot and union versions
- Low pressure spring set available
- Easy on spare parts thanks to the modular design

**Flow media**

Neutral and aggressive media with a small amount of particles/solids. The chemical resistance depends on the selected valve material ([see online tool ChemRes PLUS](#)).

**Technical data**




- ① Protective cap
- ② Central housing nut
- ③ Spindle
- ④ Upper part
- ⑤ Spring(s)
- ⑥ Pressure piece
- ⑦ Retaining ring
- ⑧ Diaphragm
- ⑨ Cartridge with piston
- ⑩ Lower part

Specification	
<b>Dimensions</b>	DN10–DN50 (3/8" – 2")
<b>Materials</b>	Parts that come into contact with medium (lower part, piston, internal housing) PVC-U, PVC-C, PP, PVDF, PTFE
	Valve upper part PP-GF (orange)
<b>Gasket materials</b>	EPDM, FKM
<b>Diaphragm</b>	EPDM, PTFE
<b>Pressure level</b>	PN10 @ +20°C (150 psi @ 68°F)
<b>Setting range</b>	Standard 0.5 – 9.0 bar (7 – 130 psi)
	Optional 0.3 – 3 bar (4 – 44 psi)
<b>Hysteresis</b>	Difference between opening and closing pressure Approx. 0.1 – 0.4 bar (1.5 – 5.8 psi)
<b>Connections</b>	Lower part with cementing or fusion spigots Lower part with true union Type connection to match all standard GF unions and inserts Available upon request: Various inserts from the GF range, e.g. transition to metal or PE
<b>Direction of flow</b>	Always corresponds to the the direction of the arrow on the lower part
<b>Assembly</b>	Threaded inserts are available for safe assembly
<b>Standards</b>	Pressure test according to ISO 9393 Leak rate according to EN 12266

### Kv 100 values

DN (mm)	Inch (inch)	d (mm)	Kv 100 (l/min)	Kv 100 (l/h)	Cv 100 (gpm)
10	3/8	16	45	2700	11.9
15	1/2	20	48	2850	12.5
20	3/4	25	112	6700	29.5
25	1	32	129	7730	34.0
32	1 1/4	40	254	15 240	67.1
40	1 1/2	50	293	17 590	77.4
50	2	63	319	19 170	84.4

### Pressure-temperature diagrams




T Temperature (°C, °F)

P Permissible pressure (bar, psi)

The pressure-temperature diagrams are based on a lifetime of 25 years and water or similar media.

## Dimensions

### Type 582 with threaded connections, cementable and fusionable spigots



### All materials

d (mm)	DN (mm)	Inch (inch)	D (mm)	H (mm)	H1 (mm)	H2 (mm)
16   20	10   15	3/8   1/2	79	132	111	21
25   32	20   25	3/4   1	100	177	148	29
40   50	32   40	1 1/4   1 1/2	147	251	207	44
63	50	2	147	251	207	44


### All materials if not labeled

d (mm)	DN (mm)	Inch (inch)	L <sup>1)</sup> PVC/PP (mm)	L <sup>1)</sup> PVDF (mm)	l2 (mm)	l3 (mm)	L4 (mm)	z PVC/PP (mm)	z PVDF (mm)
16   20	10   15	3/8   1/2	134	150	120	42	77	126	130
25   32	20   25	3/4   1	174	190	150	53	88	156	160
40   50	32   40	1 1/4   1 1/2	224	240	205	76	111	211	215
63	50	2	244	260	205	76	111	211	215

<sup>1)</sup> L only for spigot version

### Characteristics Type 582

The characteristic curves below are valid for the set range 0.5 – 9.0 bar (7 – 130 psi) and show the secondary or outlet pressure P2 over the flow Q in l/h. Parameter is the set pressure pE at Q = 0 l/h. The curves are valid for water at +20 °C and a flow velocity of 2 m/s. A special version set range 0.3 – 3 bar (4 – 44 psi) is available on request.



- Mobile apps and online tools to support configuration and calculation at [www.gfps.com/tools](http://www.gfps.com/tools)



The information and technical data (altogether "Data") herein are not binding, unless explicitly confirmed in writing. The Data neither constitutes any expressed, implied or warranted characteristics, nor guaranteed properties or a guaranteed durability. All Data is subject to modification. The General Terms and Conditions of Sale of Georg Fischer Piping Systems apply.

09/2020-A

© Georg Fischer Piping Systems Ltd, 8201 Schaffhausen/Switzerland

Tel. +41 52 631 11 11 • [www.gfps.com](http://www.gfps.com) • E-Mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)