



## Tee 90° equal PVC-U Rp

### Model:

- With parallel female thread Rp
- Connection to plastic thread only
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Rp (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	D (mm)	L (mm)
3/8	10	<b>721 201 605</b>	10	0.016	9	23	23
1/2	10	<b>721 201 606</b>	10	0.027	12	28	27
3/4	10	<b>721 201 607</b>	10	0.039	15	33	33
1	10	<b>721 201 608</b>	5	0.072	19	41	39
1 1/4	10	<b>721 201 609</b>	100	0.146	27	50	49
1 1/2	10	<b>721 201 610</b>	10	0.267	36	62	60
2	10	<b>721 201 611</b>	10	0.485	44	77	72

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>