




Adaptor bush equal PVC-U metric R

Model:

- With solvent cement socket metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U



| d | R | d | PN | Code | SP | Weight | z | L | s |
|--------|--------|------|-------|--------------------|----|--------|------|------|------|
| (inch) | (inch) | (mm) | (bar) | | | (kg) | (mm) | (mm) | (mm) |
| 3/8 | 3/8 | 16 | 16 | 721 910 705 | 10 | 0.011 | 20 | 34 | 27 |
| 1/2 | 1/2 | 20 | 16 | 721 910 706 | 10 | 0.018 | 24 | 40 | 32 |
| 3/4 | 3/4 | 25 | 16 | 721 910 707 | 10 | 0.025 | 25 | 44 | 36 |
| 1 | 1 | 32 | 16 | 721 910 708 | 10 | 0.039 | 28 | 50 | 46 |
| 1 1/4 | 1 1/4 | 40 | 16 | 721 910 709 | 10 | 0.061 | 31 | 57 | 55 |
| 1 1/2 | 1 1/2 | 50 | 16 | 721 910 710 | 10 | 0.092 | 32 | 63 | 65 |
| 2 | 2 | 63 | 16 | 721 910 711 | 5 | 0.161 | 38 | 76 | 80 |
| 2 1/2 | 2 1/2 | 75 | 10 | 721 910 712 | 6 | 0.227 | 42 | 86 | 90 |
| 3 | 3 | 90 | 10 | 721 910 713 | 5 | 0.389 | 46 | 97 | 110 |
| 4 | 4 | 110 | 10 | 721 910 714 | 5 | 0.572 | 53 | 114 | 130 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>