




## Socket PVC-C metric Rp

### Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-C



Rp (inch)	d (mm)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
½	20	16	<b>723 910 206</b>	10	0.027	4	35	32
¾	25	16	<b>723 910 207</b>	10	0.035	3	40	36
1	32	16	<b>723 910 208</b>	10	0.059	3	45	46
1 ¼	40	16	<b>723 910 209</b>	10	0.093	5	51	55
1 ½	50	16	<b>723 910 210</b>	10	0.133	7	59	65
2	63	16	<b>723 910 211</b>	5	0.211	7	69	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>