Data sheet

valid from: 7/22/21



1



PROGEF Standard Tee 90° reduced
SDR11 (PN10)

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible

[1]with IR welded reducer

	d (mm)	d1 (mm)	PN (bar)	SDR	FM	Code	SP	Weight (kg)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	e (mm)	e1 (mm)
	63	32	10	11	IR	**727 208 351**	10	0.161	65	70	25	25	5.8	2.9
	63	40	10	11	IR	**727 208 350**	10	0.165	65	70	25	25	5.8	3.7
	63	50	10	11	IR	**727 208 352**	10	0.170	65	70	25	25	5.8	4.6
	75	32	10	11	IR	**727 208 353**	5	0.238	70	75	25	25	6.8	2.9
	75	50	10	11	IR	**727 208 354**	5	0.249	70	75	25	25	6.8	4.6
	75	63	10	11	IR	**727 208 355**	5	0.258	70	75	25	25	6.8	5.8
	90	50	10	11	IR	**727 208 357**	5	0.420	80	85	25	25	8.2	4.6
	90	63	10	11	IR	**727 208 358**	5	0.428	80	85	25	25	8.2	5.8
	90	75	10	11	IR	**727 208 359**	5	0.430	80	85	25	25	8.2	6.8
	110	32	10	11	IR	**727 208 360**	5	0.652	90	95	30	25	10.0	2.9
	110	50	10	11	IR	**727 208 361**	5	0.659	90	95	30	25	10.0	4.6
	110	63	10	11	IR	**727 208 362**	5	0.665	90	95	30	25	10.0	5.8
	110	75	10	11	IR	**727 208 363**	1	0.681	90	95	30	25	10.0	6.8
	110	90	10	11	IR	**727 208 364**	1	0.701	90	95	30	25	10.0	8.2
1	125	63	10	11	IR	**727 208 365**	1	1.680	125	232	25	16	11.4	5.8
1	125	90	10	11	IR	**727 208 066**	1	1.700	125	225	25	40	11.4	8.2
1	125	110	10	11	IR	**727 208 367**	1	1.700	125	220	25	30	11.4	10.0
1	140	75	10	11	IR	**727 208 068**	1	2.400	140	245	28	41	12.7	6.8
1	140	90	10	11	IR	**727 208 069**	1	2.358	140	240	28	40	12.7	8.2
	160	63	10	11	IR	**727 208 371**	1	2.130	142	135	50	30	14.6	5.8
	160	75	10	11	IR	**727 208 372**	1	2.143	142	135	50	30	14.6	6.8
	160	90	10	11	IR	**727 208 373**	1	2.148	142	135	50	30	14.6	8.2
1	140	110	10	11	IR	**727 208 370**	1	2.380	140	245	28	33	12.7	10.0
	160	110	10	11	IR	**727 208 374**	1	2.186	142	135	50	30	14.6	10.0
	160	125	10	11	IR	**727 208 075**	1	3.600	160	272	28	32	14.6	11.4
1	200	160	10	11	IR	**727 208 385**	1	6.632	200	295	35	40	18.2	14.6
	200	180	10	11	IR	**727 208 086**	1	6.900	200	335	35	45	18.2	16.4
	225	90	10	11	IR	**727 208 388**	1	4.576	155	165	40	30	20.5	8.2
	225	110	10	11	IR	**727 208 389**	1	4.624	155	165	40	30	20.5	10.0
	225	160	10	11	IR	**727 208 391**	1	4.685	155	165	40	30	20.5	14.6
	250	160	10	11		**727 208 093**	1	12.500	227	387	68	53	22.7	14.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: http://www.gfps.com