



SYGEF Plus union (FKM white) SDR21/PN16
Gap filling O-ring positioning
High Purity clean-room product ISO Class 5 (1)

Model:

- Material: PVDF-HP
- gap filling O-ring positioning
- FDA compliant
- d75, d90 and d110 with buttress shaped thread
- Please see installation intruction

d (mm)	PN (bar)	SDR	FM	Code	Weight (kg)
20	16	21	BCF, IR	735 528 626	0.082
25	16	21	BCF, IR	735 528 627	0.123
32	16	21	BCF, IR	735 528 628	0.166
40	16	21	BCF, IR	735 528 629	0.263
50	16	21	BCF, IR	735 528 630	0.372
63	16	21	BCF, IR	735 528 631	0.463
75	16	21	BCF, IR	735 528 637	0.740
90	16	21	BCF, IR	735 528 638	0.798
110	16	21	BCF, IR	735 528 639	1.020

d (mm)	G (R/Rp BS draad) (inch)	e (mm)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)
20	1	1.9	43	106	53	53	25	37
25	1 1/4	1.9	53	112	56	56	25	38
32	1 1/2	2.4	60	118	59	59	25	40
40	2	2.4	74	124	62	62	25	41
50	2 1/4	3.0	82	130	65	65	25	43
63	2 3/4	3.0	100	136	68	68	25	44
75	S 107.5 x 3.6	3.6	133	132	66	66	24	34
90	S 107.5 x 3.6	4.3	133	130	65	65	24	48
110	S 127.5 x 3.6	5.3	155	130	65	65	25	45

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>