



O-Ring gasket EPDM/FKM

Model:

- For flange adaptors, unions and adaptor unions
- For ecoFIT, PROGEF Std/Plus, SYGEF Std
- Hardness approx. 65° Shore
- EPDM minimum temperature -40°C
- FKM minimum temperature -15°C

* For unions PVC-U, PVC-C and ABS: 21 51 01, 21 51 11, 21 53 03, 21 53 08, 21 55 04, 21 55 13, 21 55 18, 23 51 01 and 29 51 01 only

** For ecoFIT unions 753 518 612 to ...614, 753 528 612 to ...614, 753 518 412 to ...414 and 753 528 412 to ...414

Suitable for	EPDM Code	FKM Code	D (mm)	D1 (mm)	D2 (mm)
d10-20 / DN8	748 410 004	749 410 004	17.62	12.37	2.62
d16 / DN10	748 410 005	749 410 005	20.78	15.54	2.62
d16 / DN10	748 410 000	749 410 000	25.70	18.64	3.53
d20 / DN15	748 410 006	749 410 006	27.28	20.22	3.53
d25 / DN20	748 410 007	749 410 007	35.23	28.17	3.53
d25 / DN15	748 410 001	749 410 001	30.46	23.40	3.53
d32 / DN25	748 410 008	749 410 008	39.99	32.93	3.53
d40 / DN32	748 410 002	749 410 002	43.16	36.10	3.53
d40 / DN32	748 410 009	749 410 009	51.33	40.65	5.34
d40 / DN32	748 410 003	749 410 003	54.50	43.82	5.34
d50 / DN40	748 410 010	749 410 010	57.68	46.99	5.34
d60 / DN50	748 410 011	749 410 011	70.37	59.69	5.34
d63 / DN50	748 410 012	749 410 012	64.02	53.34	5.34
d75 / DN65	748 410 024	749 410 024	76.72	66.04	5.33
d75 / DN65	748 410 013	749 410 013	79.90	69.22	5.34
** d75-90 / DN65-80	748 410 014	749 410 014	92.60	81.92	5.34
* d90 / DN80	748 410 015	749 410 015	111.68	101.00	5.34
d75-90 / DN65-80	748 410 383	749 410 383	85.31	74.63	5.34
** d90-110 / DN80-100	748 410 248	749 410 248	105.30	94.62	5.34
d110 / DN100	748 410 384	749 410 384	128.68	114.70	6.99
** d110 / DN100	748 410 016	749 410 016	134.00	120.20	6.99
d125 / DN100	748 410 017	749 410 017	149.90	135.90	6.99
d140 / DN125	748 410 018	749 410 018	165.80	151.80	6.99
d160 / DN150	748 410 019	749 410 019	184.15	170.17	6.99
d200 / DN200	748 410 163	749 410 163	235.60	221.60	6.99
d250 / DN250	748 410 173	749 410 173	305.50	291.50	6.99
d280 / DN250	748 410 182	749 410 182	280.10	266.10	6.99
d315 / DN300	748 410 174	749 410 174	356.30	342.30	6.99

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>